IN THE CLAIMS:

Please cancel Claim 3 without prejudice or disclaimer of the subject matter recited therein.

Please amend Claims 1, 2, 4 and 6-12 as follows:

1.   (Currently Amended) A display apparatus, comprising:

a pair of first and second oppositely disposed substrates, at least one of which is a transparent substrate,

a display layer, disposed between said pair of first and second substrates, for bing being placed in an optical state switchable between a light transmission state and a light interruption state, for each of a plurality of pixel unit units,

a reflection surface provided on one of said first substrate pair of substrates,

a scattering layer disposed on the other said second substrate opposite to the said first substrate provided with said reflection surface, and

a light absorption structure or a light reflection structure, disposed at a boundary portion between adjacent pixels on the said first substrate provided with said reflection surface,

said structure being a light absorption structure absorbing not less than 60% of incident light.

2.   (Currently Amended) An apparatus according to Claim 1, wherein said structure is a projection~~-like structure~~ or a wall~~-like structure~~.

Claim 3.   (Cancelled).

4.   (Currently Amended) An apparatus according to ~~any one of Claims 1 - 3~~ 1, wherein the following relationship is satisfied:

$$\left| \frac{6\sqrt{2} \cdot d - 9 \cdot (2h + d) XY}{8Y^2 - X^2} \right| \leq 0.5p$$

$$x = \frac{1}{9} \left\{ 2\sqrt{2} \cos\theta + 2\sqrt{6} \sin\theta - \sqrt{9 - (\cos\theta + \sqrt{3} \sin\theta)^2} \right\},$$

$$x = \frac{1}{9} \left\{ \cos\theta + \sqrt{3} \sin\theta + 2\sqrt{18 - 2 \cdot (\cos\theta + \sqrt{3} \sin\theta)^2} \right\},$$

wherein d represents a height of said structure, p represents a pixel pitch, h represents a distance between said scattering layer and said structure, and T represents a scattering angle defined as ½ of an angle at which an intensity of light transmitted through said scattering layer while being scattered in said scattering layer is ½ of an intensity of light transmitted through said scattering layer in a straight line.

5.   (Original) An apparatus according to claim 4, wherein the height d of said structure is not less than 5 μm.

6.   (Currently Amended) An apparatus according to ~~any one of Claims 1 - 5~~ Claim 1, wherein each pixel has a rectangular shape, and said structure is disposed at a boundary portion between adjacent pixels along at least a long side of a rectangular pixel.

7.   (Currently Amended) An apparatus according to ~~any one of Claims 1 - 5~~ Claim 1, wherein each pixel has a rectangular shape having a side located at its lower portion during image formation, and said structure is disposed along said side.

8.   (Currently Amended) An apparatus according to ~~any one of Claims 1 - 7~~ Claim 1, wherein said structure has a refractive index n_w which is larger than a refractive index n_d of said display layer.

9.   (Currently Amended) An apparatus according to ~~any one of Claims 1 - 8~~ Claim 1, wherein said display layer is a liquid crystal layer.

10.   (Currently Amended) An apparatus according to ~~any one of Claims 1 - 8~~ Claim 1, wherein said display layer comprises light absorbing charged particles and a liquid for dispersing the charged particles therein.

11.   (Currently Amended) An apparatus according to Claim 10, wherein said display layer is partitioned by a partition wall for each pixel, and when said display layer is in a light transmission state, said structure is formed of the charged particles which are deposited along the partition wall.

12.   (Currently Amended) An apparatus according to ~~any one of Claims 1 - 11~~ Claim 1, wherein said apparatus has a resolution of not less than 200 pixels per inch.